

Hal E / Centerhallen

– sådan ser den ud

Adgang til hallen

På tegningen kan du se numrene for de enkelte porte, der giver adgang til hallen.

Hallens frihøjde

Hallens frihøjde, målt fra gulv til underkant af rig messelampe er 9,30 m. Se side 22-23.

Belysning

Hallen er udstyret med permanent rigkonstruktion og messelamper. Løsningen kan tilkøbes jævnfør tilbud. Til den generelle hal belysning hænger der lysarmaturer (3x58 W).

Bemærk venligst, at på bestemte tidspunkter på året, kan sollys igennem glastaget, være til gene ved brug af pc, video, osv.

Gulv

Installation af el, WS og netværk med videre sker via kanaler i hal- lens betongulv. Kanalerne ligger i hallens længderetning med en indbyrdes afstand på 15 m.

Gulvet kan klare følgende belastninger:

Hjultryk (tvillingehjul)	5.500 kg/m ²
Enkeltkraft fordelt på 15x15 cm	4.000 kg
Nyttelast*	4.000 kg/m ²

* Vægten af en lastbils last ud over lastbilens egen vægt.

Søjler

Hallens betonsøjler er 40x40 cm eller 40x80 cm.

Luft

Hallen har aircondition.

Hall E / Center Hall – a brief description

Accessing Center Hall

Please refer to the floor plan where access points are indicated.

Ceiling height

The ceiling height measured from the floor to the lower edge of the lighting truss is 9,30 m. Please see page 22-23.

General lighting

The hall is equipped with permanent lighting truss. The solution is offered according to quote. General hall light fittings (3x58 W).

Please note that at certain times of the year, sunlight from the glass roof can cause inconvenience with reflected light when using pc's, videos etc.

Floor & services

Power supplies, network and telephone cables as well as plumbing and compressed air will, where possible, be supplied via the sub-floor service ducts let into the Centre Hall's concrete floor. These run from north to south at 1 500 cm intervals throughout the length of the hall.

The floor can carry the following loads:

Wheel loads (twin wheels)	5,500 kg per sq.m.
Single-point loads per 15x15 cm	4,000 kg
Net loads*	4,000 kg per sq.m.

* (load minus weight of truck)

Pillars

A limited number of free-standing concrete pillars are to be found in the northern end of the hall. These measure 40x40 cm or 40x80 cm.

Air

The hall has air conditioning.

Hal E (Centerhal)

	3x3 m modul
	Søjle 40x80 cm
	Søjle 40x40 cm
	Brandskab, L75xB25xH85 cm, må ikke tildækkes
	Gulvkanaler med installationer
	Foldevæg
	Ingen standopbygning
	Lysrig med spot

Hall E (Center Hall)

	3x3 m modular grid
	Pillar (concrete) 40x80 cm
	Pillar (concrete) 40x40 cm
	Fire hose, cabinet L75xW25xH85 cm – must not be concealed
	Sub-floor service ducts
	Folding Wall
	No Build-up
	Lighting truss with spot

Hal E / Centerhal

Hall E / Center Hall



